## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Sunwind LED 9

Supplier's address: Logistics Manager, Rudssletta 71, 1351 Rud, NO

## Model identifier: 243209

## Type of light source:

| Lighting technology used:     | LED  | Non-directional or directional: | NDLS |  |  |
|-------------------------------|------|---------------------------------|------|--|--|
| Light source cap-type         | bulb |                                 |      |  |  |
| (or other electric interface) |      |                                 |      |  |  |
| Mains or non-mains:           | NMLS | Connected light source (CLS):   | No   |  |  |
| Colour-tuneable light source: | No   | Envelope:                       | -    |  |  |
| High luminance light source:  | No   |                                 |      |  |  |
| Anti-glare shield:            | No   | Dimmable:                       | No   |  |  |
| Product parameters            |      |                                 |      |  |  |

| Froduct parameters  |  |                         |  |              |  |  |
|---|--|-------------------------|--|--------------|--|--|
| Parameter   |  | Value                   | Parameter  | Value        |  |  |
| General product parameters:   |  |                         |  |              |  |  |
| Energy consum<br>mode (kWh/10<br>up to the neares                               | 00 h), rounded                         | 9                       | Energy efficiency<br>class   | F            |  |  |
| Useful luminous<br>dicating if it refe<br>a sphere (360°),<br>(120°) or in a na | ers to the flux in<br>, in a wide cone | 910 in<br>Sphere (360°) | Correlated colour<br>temperature,<br>rounded to the near-<br>est 100 K, or the<br>range of correlat-<br>ed colour temper-<br>atures, rounded to<br>the nearest 100 K,<br>that can be set | 2 700        |  |  |
| On-mode pow<br>pressed in W   | ver (P <sub>on</sub> ), ex-            | 9,0                     | Standby power (P <sub>sb</sub> ),<br>expressed in W and<br>rounded to the sec-<br>ond decimal  | 0,00         |  |  |
| Networked st<br>(P <sub>net</sub> ) for CLS, e<br>and rounded to<br>imal        | •                                      | -                       | Colour rendering in-<br>dex, rounded to the<br>nearest integer, or<br>the range of CRI-val-<br>ues that can be set   | 83           |  |  |
| Outer dimen-  | Height                                 | 95                      | Spectral power dis-  | See image    |  |  |
| sions without<br>separate con-<br>trol gear, light-<br>ing control              | Width<br>Depth                         | 60<br>60                | tribution in the<br>range 250 nm to 800<br>nm, at full-load  | in last page |  |  |

| parts and non-<br>lighting con-<br>trol parts, if<br>any (millime-<br>tre) |      |                              |       |  |  |
|--|------|------------------------------|-------|--|--|
| Claim of equivalent power <sup>(a)</sup>                                   | -    | If yes, equivalent power (W) | -     |  |  |
|  |      | Chromaticity coordi-         | 0,463 |  |  |
|  |      | nates (x and y)              | 0,420 |  |  |
| Parameters for LED and OLED light sources:                                 |      |                              |       |  |  |
| R9 colour rendering index value  | 5    | Survival factor              | 1,00  |  |  |
| the lumen maintenance factor   | 0,96 |                              |       |  |  |

(a)'-' : not applicable;

(b)<sub>'-'</sub> : not applicable;

